

Safety Data Sheet

according to UK REACH Regulation

Bizol Silicone+ L51

12.09.2022 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Bizol Silicone+ L51

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricating agent

1.3. Details of the supplier of the safety data sheet

Company name: BIZOL Germany GmbH
Street: Martin-Buber-Str. 12
Place: D-14163 Berlin
Telephone: +49 (30) 804 869-0

Telephone: +49 (30) 804 869-0 Telefax: +49 (30) 804 869-2860

e-mail: support@bizol.de Internet: www.bizol.com

1.4. Emergency telephone Germany: +49 (30) 804 869-0 (08.00-17.00, Mo-Fr)

number: In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 -

08454 24 24 24 In Republic of Ireland: 01 809 2166

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories: Aerosols: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

hydrocarbons, C7, n-alcanes, isoalkanes, cyclics

Signal word: Danger

Pictograms:







Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.



Safety Data Sheet

according to UK REACH Regulation

Bizol Silicone+ L51

12.09.2022 Page 2 of 8

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P260 Do not breathe aerosol.

P501 Dispose of waste according to applicable legislation.

2.3. Other hazards

Narcotic effects.

Results of PBT and vPvB assessment: not applicable.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Blend of the following materials with non-hazardous additives.

Hazardous components

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification (GB CLP Reg	ulation)				
	hydrocarbons, C7, n-alcane	25 - < 50 %				
	927-510-4		01-2119475515-33			
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411					
74-98-6	propane	20 - < 25 %				
	200-827-9	601-003-00-5	01-2119486944-21			
	Flam. Gas 1, Compressed g					
106-97-8	butane	12,5 - < 20 %				
	203-448-7	601-004-00-0	01-2119474691-32			
	Flam. Gas 1, Compressed g					
75-28-5	isobutane	12,5 - < 20 %				
	200-857-2	601-004-00-0	01-2119485395-27			
	Flam. Gas 1, Compressed g					

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

When in doubt or if symptoms are observed, get medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.



Safety Data Sheet

according to UK REACH Regulation

Bizol Silicone+ L51

Revision date:

12.09.2022 Page 3 of 8

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO2).

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO2). Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Protective measures: see section 7 + 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Protective measures: see section 7 + 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

Advice on protection against fire and explosion

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment. Therefore keep away from fire and sources of ignition. Provide earthing of containers, equipment, pumps and ventilation facilities. Use non-sparking tools. Recommendation: Wear anti-static footwear and clothing

Advice on general occupational hygiene

When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Protect against: Frost. Keep away from heat. Protect from direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Revision No: 1,2 - Replaces version: 1



Revision date: 12.09.2022

Safety Data Sheet

according to UK REACH Regulation

Bizol Silicone+ L51

Page 4 of 8

Print date: 08.10.2022

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift

Y: A risk of reproductive effects needs not to be feared if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

Z: A risk of reproductive effects cannot to be excluded if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

blood (B)

Urine (U)

8.2. Exposure controls

Appropriate engineering controls

See section 7. No additional measures necessary.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye glasses with side protection.

Hand protection

Wear suitable gloves. Recommended glove articles: EN ISO 374. Suitable material: NBR (Nitrile rubber). Breakthrough time: > 120 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Skin protection

Protective clothing.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protection apparatus: Filtering Half-face mask (EN 149), e.g. FFA P / Full-/half-/quarter-face masks (EN 136/140) + Combination filtering device, e.g. A P.

GB - EN

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: colourless
Odour: characteristic

Melting point/freezing point:

Boiling point or initial boiling point and

not determined
not applicable

boiling range: Flammability

Solid/liquid: Extremely flammable aerosol.
Gas: not applicable
Lower explosion limits: 0,9 vol. %
Upper explosion limits: 10,9 vol. %
Flash point: < 0 °C
Auto-ignition temperature: > 230 °C
Decomposition temperature: not determined



Safety Data Sheet

according to UK REACH Regulation

Bizol Silicone+ L51

12.09.2022 Page 5 of 8

pH-Value: not determined
Viscosity / kinematic: not determined
Water solubility: Immiscible
Partition coefficient n-octanol/water: not determined
Vapour pressure: 8300 hPa

(at 20 °C)

Density (at 20 °C): 0,64 g/cm³
Relative vapour density: not determined
Particle characteristics: not applicable

9.2. Other information

Explosive properties

The product is: not explosive. Heating causes rise in pressure with risk of bursting. In use may form flammable/explosive vapour-air mixture.

Other safety characteristics

Pour point: not determined Viscosity / dynamic: not determined Flow time: not determined

No further relevant information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (hydrocarbons, C7, n-alcanes, isoalkanes, cyclics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards



Safety Data Sheet

according to UK REACH Regulation

Bizol Silicone+ L51

12.09.2022 Page 6 of 8

Other information

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36
106-97-8	butane	2,89
75-28-5	isobutane	2,8

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

List of Wastes Code - residues/unused products

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08);

waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures;

hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE

CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal

packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Safety Data Sheet

according to UK REACH Regulation

Bizol Silicone+ L51

12.09.2022 Page 7 of 8



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS (naphtha (petroleum), hydrotreated light)

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Marine pollutant: YES

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: naphtha (petroleum), hydrotreated light

14.6. Special precautions for user

No data available

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information



Safety Data Sheet

according to UK REACH Regulation

Bizol Silicone+ L51

12.09.2022 Page 8 of 8

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40

2010/75/EU (VOC): 92 % (584,5 g/l)

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,7,9,11,13,14,15.

Abbreviations and acronyms

ADR: Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

CAS: Chemical Abstracts Service (a division of the American Chemical Society)

DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average STEL (EC): Short Term Exposure Limit

ATE: Acute Toxicity Estimate

LD50: Lethal Dose, 50% (median lethal dose)

LC50: Lethal Concentration, 50% (median lethal concentration)

EC50: half maximal Effective Concentration ErC50: EC50 in terms of reduction of growth rate

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
LISSE	May agua drawainaga ar dizzinaga

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Further Information

Safety Data Sheet according to COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)